



Pyure Slimline[™] Hydroxyl Generator Air & Surface Protection

Product Specifications







Slimline[™] Purifier

The Slimline[™] hydroxyl generating purifier is designed for smaller spaces where a portable or wall-mounted unit is sought. It is ideal for offices and schools, senior living, conference and waiting rooms, and other commercial applications that need to sanitize and deodorize indoor spaces.

The table below summarizes the minimum treatment area in absence of ventilation, and the treatment area range under typical conditions: 3 air changes per hour, 90% recirculated air and 2.7 meters ceilings. These guidelines should be adhered to for optimal performance and safety.

Operating Guideline

Minimum Area (if there is no air circulation) 22m²

Treatment Range 20 - 84m²

Specifications

Dimensions (LxWxD) 457mm x 133mm x 635mm

Weight 7.9kg

Voltage 230V @ 50Hz
Power 170 Watts (Max)

Number of Optics 1

Noise Level 52.8dBA - 69.9dBA

Airflow* 180 CFM *Airflows were measured with new/clean units

Filter Washable filter 127mm x 317.5mm x 6.4mm

Shipping Dimensions 533mm x 229mm x 737mm

Shipping Weight 9.8kg

Certification UL 507, CSA C22.2 #113, CE, RoHS, REACH

Warranty 2 years covering defects in workmanship or materials, but excluding spare parts and

consumables



MIKROBE

Distributed by:

post@mikrobe.no www.mikrobe.no

Copyright 2022, The Pyure Company. Slimline™is a trademark of The Pyure Company, Boynton Beach, FL 33426 USA